



RENO

SLT OF RANGE

PUSHING SILENCE FURTHER.

INTRODUCING THE NEW SLT OF RANGE

THE SLT OF SERIES: ENGINEERED FOR MORE COMFORT, SAME TOP PERFORMANCE.

With noise as low as 59 dB(A), the SLT OF series works quietly, never getting in your way.

A compact Italian designed pump powers the SLT OF series—available in 1 and 2 hp, reaching 9 bar for professional tool use.

Available with 6, 20 or 24-litre tanks, SLT OF adapts to any application.

SLT OF’s oil-free, direct-drive design ensures low maintenance and reliable air supply.

Easy maintenance

Oil-free and direct-driven, SLT OF needs minimal maintenance—more uptime, less hassle.

Silence and Compactness

High output, low footprint: up to 230 l/min from a silent, compact unit.

Safety

Stay safe—the enclosed pump keeps hands clear of heat and motion.

Versatile

High pressure, high capability: SLT OF reaches 9 bar for specialist use.

Plug and Play

Quick access: on/off button right on the control panel.

IDEAL FOR A WIDE RANGE OF APPLICATIONS

	Inflating	Blowing	Spray - Painting	Hobby painting	Nailing and stapling	Washing	Professional washing	Impact wrenching
SLT OF 1/6	x	x	x	x	x	—	—	—
SLT OF 2/20	x	x	x	x	x	—	—	—
SLT OF 2/24	x	x	x	x	x	x	x	x

SLT OF 1/6



- Strain-Free Mobility** — Built to go: light and easy to carry.
- Accessible** — Fully equipped, compact control system.
- Vibration-Free** — Anti-vibration rubber pads cut noise and movement.

SLT OF 2/20



- Natural** — Shaped for comfort—ergonomic handle included.
- Streamlined** — Pump enclosure cuts noise and shields moving parts.
- Orderly work station** — Secure your cables with the built-in double hook.
- Smooth-gliding** — Transport made simple with built-in wheels.
- Straightforward functionality** — Simplified control with a spacious, visible interface.

SLT OF 2/24



- Non-slip** — Soft grip ensures easy handling.
- Simplified controls** — All-in-one, compact instrument panel.
- Compact and portable** — Additional handle boosts portability.
- Anti-tip** — Two feet prevent tipping.
- Smooth-gliding** — Robust wheels simplify maneuvering.

NOISE LEVELS

Decibel



dB(A)

20

40

59

62

80

100

140



SLT OF RANGE

PERFORMANCE BENCHMARKS

Model	Art. no.	Motor			Pressure	Air displacement	Vessel	LpA	Weight	Dimensions	
		V	kW	hp	rpm	bar	L/min.	L	dB(A)	kg	L x W x H (mm)
SLT OF 1/6	1129741352	230/50/1	0.75	1	1420	9	140	6	59	20	380 x 300 x 540
SLT OF 2/20	1129741350	230/50/1	1.5	2	1420	9	230	20	62	33	495 x 410 x 800
SLT OF 2/24	1129741351	230/50/1	1.5	2	1420	9	230	24	62	28	630 x 310 x 605



Reno A/S | +45 70 10 22 10 | forhandlere@reno-ff.com | www.reno.dk

© 2025, A.ARIA C. S.r.l. All rights reserved.
A.ARIA C. S.r.l. reserves the right to change or revise specifications and product design in connection with any features of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions or replacements for equipment previously sold or shipped. Read all safety instructions in the manual before usage.

6999220010